



SAFETY DATA SHEET

ARCO SURVEY SPRAY PAINT 750ML YELLOW 5717807

Page: 1

Compilation date: 17/04/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ARCO SURVEY SPRAY PAINT 750ML YELLOW 5717807

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: LMA Services Ltd
Halifax Way
Pocklington Industrial Estate
Pocklington
York
YO42 1NR
United Kingdom
Tel: 01759 304676
Fax: 01759 305809
Email: technical@aerosol.uk.com

1.4. Emergency telephone number

Emergency tel: 01759 304676
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F+: R12; Xi: R36; N: R51/53; -: R64; -: R66; -: R67

Classification under CLP: STOT SE 3: H336; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Aerosol 1: H222;
Lact.: H362; -: EUH208; -: H229

Most important adverse effects: Extremely flammable. Irritating to eyes. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause harm to breastfed babies.
Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains isodecyloxpropylamine acetate. May produce an allergic reaction.
H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

[cont...]

SAFETY DATA SHEET

ARCO SURVEY SPRAY PAINT 750ML YELLOW 5717807

Page: 2

H362: May cause harm to breast-fed children.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

GHS09: Environmental



Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P263: Avoid contact during pregnancy.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Label elements under CHIP:

Hazard symbols: Extremely flammable.

Irritant.

Dangerous for the environment.



Risk phrases: R12: Extremely flammable.

R36: Irritating to eyes.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R64: May cause harm to breastfed babies.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.

S29: Do not empty into drains.

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

S23: Do not breathe gas/fumes/vapour/spray.

S24/25: Avoid contact with skin and eyes.

Precautionary phrases: Contains isodecyloxpropylamine acetate. May produce an allergic reaction.

Pressurised container: protect from sunlight and do not expose to temperatures

[cont...]

SAFETY DATA SHEET

ARCO SURVEY SPRAY PAINT 750ML YELLOW 5717807

Page: 3

exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETONE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-662-2	67-64-1	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	30-50%

PROPANE

200-827-9	74-98-6	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
-----------	---------	---	-------------------------------------	--------

BUTANE

203-448-7	106-97-8	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	----------	---	-------------------------------------	-------

N-BUTYL ACETATE

204-658-1	123-86-4	-: R10; -: R66; -: R67	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	------------------------	--	-------

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC.; LOW BOILING POINT NAPHTHA

265-199-0	64742-95-6	Xn: R65; Xi: R37; N: R51/53; -: R10; -: R66; -: R67	-	1-10%
-----------	------------	---	---	-------

ISOBUTANE

200-857-2	75-28-5	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	---------	---	-------------------------------------	-------

1,2,4-TRIMETHYLBENZENE

202-436-9	95-63-6	-: R10; Xn: R20; Xi: R36/37/38; N: R51/53	Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	1-10%
-----------	---------	---	---	-------

[cont...]

SAFETY DATA SHEET

ARCO SURVEY SPRAY PAINT 750ML YELLOW 5717807

Page: 4

1-METHOXY-2-PROPANOL

203-539-1	107-98-2	-: R10; -: R67	Flam. Liq. 3: H226; STOT SE 3: H336	1-10%
-----------	----------	----------------	-------------------------------------	-------

2-BUTOXYETHANOL

203-905-0	111-76-2	Xn: R20/21/22; Xi: R36/38	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%
-----------	----------	---------------------------	---	-------

ETHYL ACETATE

205-500-4	141-78-6	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---------------------------------	---	-------

ALKANES, C14-17, CHLORO

287-477-0	85535-85-9	-: R64; -: R66; N: R50/53	Lact.: H362; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	1-10%
-----------	------------	---------------------------	--	-------

ISODECYLOXPROPYLAMINE ACETATE

-	28701-67-9	Xn: R22; C: R34; Xi: R37; N: R50/53; Sens.: R43	Acute Tox. 4: H302; Skin Corr. 1B: H314; STOT SE 3: H335; Aquatic Chronic 1: H410; Skin Sens. 1: H317	0.1-1%
---	------------	--	---	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

[cont...]

SAFETY DATA SHEET

ARCO SURVEY SPRAY PAINT 750ML YELLOW 5717807

Page: 5

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. If outside do not approach from downwind.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may produce sparks. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

[cont...]

SAFETY DATA SHEET

ARCO SURVEY SPRAY PAINT 750ML YELLOW 5717807

Page: 6

Hazardous ingredients:

ACETONE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m3	3620 mg/m3	-	-

PROPANE

UK	1800 mg/m3	7200 mg/m3	-	-
----	------------	------------	---	---

BUTANE

UK	1450 mg/m3	1810 mg/m3	-	-
----	------------	------------	---	---

N-BUTYL ACETATE

UK	724 mg/m3	966 mg/m3	-	-
----	-----------	-----------	---	---

ISOBUTANE

UK	2400 mg/m3	9600 mg/m3	-	-
----	------------	------------	---	---

1,2,4-TRIMETHYLBENZENE

UK	125 mg/m3	-	-	-
----	-----------	---	---	---

1-METHOXY-2-PROPANOL

UK	375 mg/m3	560 mg/m3	-	-
----	-----------	-----------	---	---

2-BUTOXYETHANOL

UK	25 ppm	50 ppm	-	-
----	--------	--------	---	---

ETHYL ACETATE

UK	200 ppm	400 ppm	-	-
----	---------	---------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Chemically resistant gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Yellow

[cont...]

SAFETY DATA SHEET

ARCO SURVEY SPRAY PAINT 750ML YELLOW 5717807

Page: 7

Odour: Characteristic odour

Flash point°C: -60

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

[cont...]

SAFETY DATA SHEET

ARCO SURVEY SPRAY PAINT 750ML YELLOW 5717807

Page: 8

1-METHOXY-2-PROPANOL

IVN	RAT	LD50	4200	mg/kg
ORL	MUS	LD50	11700	mg/kg
ORL	RAT	LDLO	3739	mg/kg

2-BUTOXYETHANOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: No data available.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

ACETONE

BLUEGILL (<i>Lepomis macrochirus</i>)	LC50	8300	mg/l
---	------	------	------

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

[cont...]

SAFETY DATA SHEET

ARCO SURVEY SPRAY PAINT 750ML YELLOW 5717807

Page: 9

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Not applicable.

Disposal of packaging: Not applicable.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

[cont...]

SAFETY DATA SHEET

ARCO SURVEY SPRAY PAINT 750ML YELLOW 5717807

Page: 10

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.
EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.
H220: Extremely flammable gas.
H222: Extremely flammable aerosol.
H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H229: Pressurised container: May burst if heated
H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.
H362: May cause harm to breast-fed children.
H410: Very toxic to aquatic life with long lasting effects.
H411: Toxic to aquatic life with long lasting effects.
R10: Flammable.
R11: Highly flammable.
R12: Extremely flammable.
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R20: Harmful by inhalation.
R22: Harmful if swallowed.
R34: Causes burns.
R36/37/38: Irritating to eyes, respiratory system and skin.
R36/38: Irritating to eyes and skin.
R36: Irritating to eyes.
R37: Irritating to respiratory system.
R43: May cause sensitisation by skin contact.

[cont...]

SAFETY DATA SHEET

ARCO SURVEY SPRAY PAINT 750ML YELLOW 5717807

Page: 11

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R64: May cause harm to breastfed babies.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.