

Honeywell



4403603 / SS TO S620511

SAFETY DATA SHEET

Holts Professional Floor Paint

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: Holts Professional Floor Paint

PART No.: HPF6

IN-HOUSE No.: LSFP

SUPPLIER: Holt Lloyd
Oakhurst Drive
Cheadle
Manchester
Tel: +44 (0)161 491 7391
Fax: +44 (0)161 491 7399

EMERGENCY TELEPHONES: Out of office hours: +44 (0)786 675 5247

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME	CAS No.:	CONTENT	SYMBOL:	RISK:
SOLVENT NAPHTHA (PETROLEUM)	64742-48-9	25-50 %	Xn	R-10, 65, 66

3. HAZARDS IDENTIFICATION:

Flammable. Repeated exposure may cause skin dryness or cracking.

4. FIRST AID MEASURES:

GENERAL: Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION: Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering 100% oxygen.

INGESTION: DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately! Provide rest, warmth and fresh air.

SKIN: Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

EYES: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA: Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES: Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

6. ACCIDENTAL RELEASE MEASURES:

SPILL CLEANUP METHODS: Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer. Inform Authorities if large amounts are involved.

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS: Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Risk of vapour concentration on the floor and in low lying areas.

STORAGE PRECAUTIONS: Keep in cool, dry, ventilated storage and closed containers. Keep in original container.

STORAGE CRITERIA: Flammable liquid storage.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT COMMENTS: OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT:



VENTILATION: Provide adequate general and local exhaust ventilation.

RESPIRATORS: No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Level (OEL).

PROTECTIVE GLOVES: Use protective gloves.

EYE PROTECTION: Wear approved safety goggles.

OTHER PROTECTION: Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENIC WORK PRACTICES: DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. No eating or drinking while working with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE:	Viscous. Liquid.		
COLOUR:	Yellow.		
ODOUR/TASTE:	Characteristic.		
DENSITY/SPECIFIC GRAVITY (g/ml):	1.16	Temperature (°C):	
VISCOSITY (interval):	70 - 80 cSt	Temperature (°C):	23
SOLUBILITY DESCRIPTION:	Immiscible with water.		
FLASH POINT (°C):	40°C	Method:	N/A.

10. STABILITY AND REACTIVITY:

STABILITY:	Normally stable.
CONDITIONS TO AVOID:	Avoid contact with acids and oxidising substances.
HAZARDOUS DECOMP. PRODUCTS:	Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO), Carbon dioxide (CO ₂), Nitrous gases (NO _x).

11. TOXICOLOGICAL INFORMATION:

INHALATION:	Prolonged inhalation of high concentrations may damage respiratory system.
INGESTION:	Liquid irritates mucous membranes and may cause abdominal pain if swallowed.
SKIN:	Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.
EYES:	May cause severe irritation to eyes.
TARGET ORGANS:	Skin. Eyes. Respiratory system, lungs.

12. ECOLOGICAL INFORMATION:

ECOLOGICAL INFORMATION:	No data is available on the product itself
-------------------------	--

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS:	Dispose of in accordance with Local Authority requirements. Do not allow runoff to sewer, waterway or ground.
-------------------	---

14. TRANSPORT INFORMATION:

GENERAL: LIMITED QUANTITIES derogation applies to package volumes under 5Lt.


LABEL FOR CONVEYANCE:



UN No. ROAD: 1263
ADR CLASS No.: 3
ADR CLASS: Class 3: Flammable liquids.
ADR ITEM No.: III
ADR LABEL No.: 3
HAZCHEM CODE: 3Y
CEFIC TEC(R) No.: 30G30
PROPER SHIPPING NAME I: PAINT
RID CLASS No.: 3
RID ITEM No.: III
UN No. SEA: 1263
IMDG CLASS: 3.3
IMDG PACK GR.: III
EmS No.: 3-05
MARINE POLLUTANT: Yes.
UN No., AIR: 1263
ICAO CLASS: 3
AIR PACK GR.: III

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY: NC Not classified Fo Flammable



RISK PHRASES: R-10 Flammable.
R-66 Repeated exposure may cause skin dryness or cracking.

SAFETY PHRASES: S-2 Keep out of reach of children.
S-16 Keep away from sources of ignition - No Smoking.
S-26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S-28 After contact with skin, wash immediately with plenty of water.
S-38 In case of insufficient ventilation, wear suitable respiratory equipment.
S-46 If swallowed seek medical advice immediately and show this container label.
S-51 Use only in well ventilated areas.
S-24/25 Avoid contact with skin and eyes.

STATUTORY INSTRUMENTS: Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE: Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES: Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION:

ISSUED BY: Colin Sawmy

REV. No./REPL. SDS GENERATED: 1/

SDS No.: 10474

SAFETY DATA SHEET STATUS: Approved.

DATE: 23/01/02

PRINTING DATE: 2002-01-23