



SAFETY DATA SHEET COLOUR MATCH AEROSOL PAINT

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	COLOUR MATCH AEROSOL PAINT
Product number	QGB014,QMB014,WPF012,WPF014,WPF015,WPF018,WPF021,YAB001,YAB007,YAB021, YAB023,YAB033,YAB055,YAB060,YAB062,YAB066,YAB070,YAB091,YAB095,YAB096,YAB 097,YAB098,YAB099,YAB100,YAB101,YAB119,YAB121,YAB123,YAB125,YAB127,YAB128, YAB131,YAB134,YAB135,YAB137,YAB138,YAB140,YAB141,YAB143,YAB145,YAB148,YAB 149,YAB150,YAB157,YAB158,YAB162,YAB163,YAB164,YAB165,YAB166,YAB167,YAB168, YAB169,YAB172,YAB173,YAB174,YAB176,YAB177,YAB179,YAB180,YAB181,YAB182,YAB 186,YAB191,YAB192,YAB193,YAB196,YAC002,YAD009,YAD015,YAD018,YAD020,YAD022 ,YAD023,YAD027,YAD028,YAD029,YAD033,YAD036,YAD037,YAD038,YAD039,YAF011, YA F030,YAF038,YAF040,YAF048,YAF058,YAF059,YAF064,YAF066,YAF067,YAF068,YAF072, YAF073,YAF074,YAF076,YAF077,YAF078,YAF079,YAF081,YAF082,YAF083,YAF085,YAF0 86,YAF088,YAF089,YAF093,YAF095,YAF103,YAF107,YAF108,YAF115,YAF117,YAF119, YA F120,YAF127,YAF128,YAF132,YAF135,YAF136,YAF137,YAF139,YAF140,YAF144,YAF146, YAF147,YAF148,YAF149,YAF150,YAF151,YAF153,YAF154,YAF155,YAF156,YAF158,YAF1 59,YAF160,YAF162,YAF163,YAF164,YAF166,YAF167,YAF169,YAF170,YAF172,YAF175, YA F176,YAF177,YAF179,YAF180,YAF182,YAF183,YAF184,YAL005,YAG004,YAO003,YAG005 ,YAR030,YAR054,YAG134,YAR063,YAR077,YAR087,YAR090,YAR097,YAV022,YAV054, YA V058,YAV061,YAV064,YAV069,YAV072,YAV074,YAV075,YAV076,YAV084,YAV085,YAV08 7,YAV088,YAV089,YAV090,YAV091,YAV094,YAV101,YAV102,YAV105,YAV106,YAV107, YA V110,YAV116,YAV118,YAV120,YAV121,YAV124,YAW025,YAW026,YAW028,YAW038,YAW 046,YAX018,YAY021,YGB014,YGW014,YMB014,YAW345,YAW346,YMW001,YMW002, YA W347,YMW003,YNC001,YNC002,YNC003,YNC004,YNC005,YNC006,YNC007,YNC008, YN C009,YNC010,YNC011,YNC012,YNC013,YNC014,YNC015,YNC016,YNC017,YNC018, YNC 019,YNC020,YNC021,YNC022,YNC023,YNC024,YNC025,YNC026,YNC027,YNC028, YNC0 29,YPA014,YSB014,YTA001,YTA005

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Paint.
------------------------	--------

1.3. Details of the supplier of the safety data sheet

Supplier	TETROSYL LIMITED Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com
-----------------	---

COLOUR MATCH AEROSOL PAINT

Manufacturer TETROSYL LIMITED
 Bury
 Lancashire
 England
 BL9 7NY

0161 764 5981
 0161 797 5899
 info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone 0161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Dam. 1 - H318 STOT SE 3 - H336

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi;R36. F+;R12. R66,R67.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H318 Causes serious eye damage.
 H229 Pressurised container: may burst if heated
 H222 Extremely flammable aerosol.
 H336 May cause drowsiness or dizziness.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing vapour/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container in accordance with national regulations.

COLOUR MATCH AEROSOL PAINT

Contains ACETONE, BUTYL ACETATE -norm, ISO-BUTANOL

Supplementary precautionary statements P312 Call a POISON CENTER/doctor if you feel unwell.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ACETONE	30-60%
----------------	---------------

CAS number: 67-64-1

EC number: 200-662-2

Classification

Flam. Liq. 2 - H225

Eye Irrit. 2 - H319

STOT SE 3 - H336

Classification (67/548/EEC or 1999/45/EC)

F;R11 Xi;R36 R66 R67

PETROLEUM GASES, LIQUEFIED	10-30%
-----------------------------------	---------------

CAS number: 68476-85-7

EC number: 270-704-2

Classification

Flam. Gas 1 - H220

Classification (67/548/EEC or 1999/45/EC)

F+;R12.

BUTYL ACETATE -norm	10-30%
----------------------------	---------------

CAS number: 123-86-4

EC number: 204-658-1

Classification

Flam. Liq. 3 - H226

STOT SE 3 - H336

Classification (67/548/EEC or 1999/45/EC)

R10 R66 R67

XYLENE	1-5%
---------------	-------------

CAS number: 1330-20-7

EC number: 215-535-7

Classification

Flam. Liq. 3 - H226

Skin Irrit. 2 - H315

Acute Tox. 4 - H312

Acute Tox. 4 - H332

Classification (67/548/EEC or 1999/45/EC)

R10 Xn;R20/21 Xi;R38

ISO-BUTANOL	1-5%
--------------------	-------------

CAS number: 78-83-1

EC number: 201-148-0

REACH registration number: 01-2119484609-23-XXXX

Classification

Flam. Liq. 3 - H226

Skin Irrit. 2 - H315

Eye Dam. 1 - H318

STOT SE 3 - H335, H336

Classification (67/548/EEC or 1999/45/EC)

R10 Xi;R37/38,R41 R67

COLOUR MATCH AEROSOL PAINT

2-METHOXY-1-METHYLETHYL ACETATE		1-5%
CAS number: 108-65-6	EC number: 203-603-9	REACH registration number: 01-2119475791-29
Classification		Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226		R10
HYDROCARBONS, C9-12, N-ALKANES, ISOALKANES, CYCLICS, (2-25%) AROMATICS		<1%
CAS number: —	EC number: 919-446-0	REACH registration number: 01-2119458049-33-XXXX
Classification		Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226		Xn;R65. N;R51/53. R10,R66,R67.
STOT SE 3 - H336		
STOT RE 1 - H372		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Effects may be delayed. Keep affected person under observation.
Inhalation	Remove affected person from source of contamination. If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. Get medical attention. Show this Safety Data Sheet to the medical personnel. Symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Keep affected person under observation. Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin contact	Wash skin thoroughly with soap and water. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation.
----------------------------	---

COLOUR MATCH AEROSOL PAINT

Inhalation	May cause an asthma-like shortness of breath. In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Drowsiness, dizziness, disorientation, vertigo. Vapours may cause drowsiness and dizziness. Vapours in high concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Central nervous system depression.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. Due to the physical nature of this material it is unlikely that swallowing will occur.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. May cause skin irritation/eczema.
Eye contact	Severe irritation, burning and tearing. Vapour, spray or dust may cause chronic eye irritation or eye damage. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Foam, carbon dioxide or dry powder. Water spray. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
---------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Extremely flammable. Severe explosion hazard when vapours are exposed to flames. Risk of explosion if heated. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up. Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting	Risk of re-ignition after fire has been extinguished. Risk of explosion. Cool containers exposed to flames with water until well after the fire is out. Use water to keep fire exposed containers cool and disperse vapours.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours. In case of spills, beware of slippery floors and surfaces.
-----------------------------	---

6.2. Environmental precautions

COLOUR MATCH AEROSOL PAINT

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up For waste disposal, see Section 13. If leakage cannot be stopped, evacuate area. Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not use in confined spaces without adequate ventilation and/or respirator. Mechanical ventilation or local exhaust ventilation may be required. Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep containers upright. Protect against physical damage and/or friction. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Do not store for long periods. Do not store in large quantities. Store in a cool and well-ventilated place. Keep container dry. Do not store near heat sources or expose to high temperatures.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

PETROLEUM GASES, LIQUEFIED

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

Carc

BUTYL ACETATE -norm

COLOUR MATCH AEROSOL PAINT

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

ISO-BUTANOL

Long-term exposure limit (8-hour TWA): WEL 50 ppm 154 mg/m³

Short-term exposure limit (15-minute): WEL 75 ppm 231 mg/m³

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m³(Sk)

HYDROCARBONS, C9-12, N-ALKANES, ISOALKANES, CYCLICS, (2-25%) AROMATICS

Long-term exposure limit (8-hour TWA): WEL 600 mg/m³

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit

Carc = Capable of causing cancer and/or heritable genetic damage.

Sk = Can be absorbed through skin.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients. Use explosion-proof general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

No specific hand protection recommended. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Provide eyewash station. Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Wash contaminated clothing before reuse. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Do not smoke in work area. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Various colours.
Odour threshold	Scientifically unjustified. Scientifically unjustified.
pH	Scientifically unjustified.

COLOUR MATCH AEROSOL PAINT

Melting point	Scientifically unjustified.
Initial boiling point and range	Technically not feasible.
Flash point	Technically not feasible.
Evaporation rate	Scientifically unjustified.
Upper/lower flammability or explosive limits	Scientifically unjustified.
Vapour pressure	Scientifically unjustified.
Vapour density	Scientifically unjustified.
Relative density	0.87 @ 20°C
Solubility(ies)	Insoluble in water.
Partition coefficient	Scientifically unjustified. : -0.24/0.58
Auto-ignition temperature	Scientifically unjustified.
Decomposition Temperature	Scientifically unjustified.
Viscosity	<50 cP @ 20°C
Oxidising properties	Not determined.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product. Vapours may form explosive mixtures with air.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not relevant.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

COLOUR MATCH AEROSOL PAINT

ATE dermal (mg/kg) 35,341.37

Acute toxicity - inhalation

ATE inhalation (gases ppm) 144,578.31

ATE inhalation (vapours mg/l) 353.41

ATE inhalation (dusts/mists mg/l) 48.19

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility No evidence of reproductive toxicity in animal studies.

Specific target organ toxicity - single exposure

STOT - single exposure Central nervous system depression including narcotic effects such as drowsiness, narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Morphological changes that are potentially reversible but provide clear evidence of marked organ dysfunction.

Target organs Skin

Aspiration hazard

Aspiration hazard Not applicable.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Gas or vapour is harmful on prolonged exposure or in high concentrations.

Ingestion

No harmful effects expected from quantities likely to be ingested by accident.

Skin contact

Repeated exposure may cause skin dryness or cracking.

Eye contact

Irritating to eyes.

Acute and chronic health hazards

This chemical can be hazardous when inhaled and/or touched. This product is corrosive. This product may cause skin and eye irritation. Prolonged contact may cause burns. May cause severe internal injury. Vapour from this product may be hazardous by inhalation.

Route of entry

Inhalation Ingestion. Skin and/or eye contact Skin absorption

Target organs

Central nervous system Eyes Skin

Medical symptoms

Skin irritation. Irritation of eyes and mucous membranes. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.

Medical considerations

Skin disorders and allergies. Pre-existing eye problems.

SECTION 12: Ecological Information

Ecotoxicity

Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

Acute toxicity - fish

LC₅₀, 96 hours: 2000 (Acetone) mg/l, Fish

COLOUR MATCH AEROSOL PAINT

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 10 (Acetone) mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Scientifically unjustified. : -0.24/0.58

12.4. Mobility in soil

Mobility The product is insoluble in water.

Adsorption/desorption coefficient Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Do not puncture or incinerate, even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

COLOUR MATCH AEROSOL PAINT

ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ADN packing group	None
ICAO packing group	None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	20/11/2015
Revision	12

COLOUR MATCH AEROSOL PAINT

Supersedes date	30/10/2013
SDS status	Approved.
Risk phrases in full	R10 Flammable. R11 Highly flammable. R12 Extremely flammable. R20/21 Harmful by inhalation and in contact with skin. R36 Irritating to eyes. R37/38 Irritating to respiratory system and skin. R38 Irritating to skin. R41 Risk of serious damage to eyes. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H228 Flammable solid. H229 Pressurised container: may burst if heated H261 In contact with water releases flammable gases. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.