



## Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 20

LOCTITE 243

SDS No. : 316211

V009.9

Revision: 07.11.2019

printing date: 30.11.2019

Replaces version from: 09.07.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE 243

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:  
Adhesive

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd  
Adhesives  
Wood Lane End  
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 2

H411 Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Label elements (CLP):

Hazard pictogram:



Contains

Tetramethylene dimethacrylate

	maleic acid
	Acetic acid, 2-phenylhydrazide
<b>Signal word:</b>	Warning
<b>Hazard statement:</b>	H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.
<b>Precautionary statement:</b>	***** ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements***
<b>Precautionary statement: Prevention</b>	P273 Avoid release to the environment. P280 Wear protective gloves.
<b>Precautionary statement: Response</b>	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

**2.3. Other hazards**

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****General chemical description:**

Anaerobic adhesive

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Tetramethylene dimethacrylate 2082-81-7	218-218-1 01-2119967415-30	25- 50 %	Skin Sens. 1B H317
2,4,6-Triallyloxy-s-triazine 101-37-1	202-936-7 01-2119489756-17	5- < 10 %	Acute Tox. 4; Oral H302 Aquatic Chronic 2 H411
2-[[[2,2-bis[[[(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	302-434-9 01-2119977121-41	1- < 5 %	Eye Irrit. 2 H319 Aquatic Chronic 2 H411
Fatty acid amide 126098-16-6	484-050-2 01-0000020228-74	0,25- < 2,5 %	Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10
α, α-dimethylbenzyl hydroperoxide 80-15-9	201-254-7 01-2119475796-19	0,1- < 1 %	Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314
Acetic acid, 2-phenylhydrazide 114-83-0	204-055-3	0,1- < 1 %	Acute Tox. 3; Oral H301 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3; Inhalation H335 Carc. 2 H351
maleic acid 110-16-7	203-742-5 01-2119488705-25	0,1- < 1 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3 H335
1,4-Naphthalenedione 130-15-4	204-977-6	0,01- < 0,1 %	Acute Tox. 3; Oral H301 Skin Irrit. 2; Dermal H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 Acute Tox. 1; Inhalation H330 STOT SE 3; Inhalation H335 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10

For full text of the H - statements and other abbreviations see section 16 "Other information".  
Substances without classification may have community workplace exposure limits available.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

###### Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

###### Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

###### Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

##### 4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

Prolonged or repeated contact may cause eye irritation.

##### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### Suitable extinguishing media:

Carbon dioxide, foam, powder

Fine water spray

###### Extinguishing media which must not be used for safety reasons:

None known

##### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

##### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

###### Additional information:

In case of fire, keep containers cool with water spray.

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Wear protective equipment.

##### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

##### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

**6.4. Reference to other sections**  
See advice in section 8

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Use only in well-ventilated areas.  
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.  
Avoid skin and eye contact.  
See advice in section 8

**Hygiene measures:**

Good industrial hygiene practices should be observed.  
Do not eat, drink or smoke while working.  
Wash hands before work breaks and after finishing work.

**7.2. Conditions for safe storage, including any incompatibilities**

Ensure good ventilation/extraction.  
Refer to Technical Data Sheet  
Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

**7.3. Specific end use(s)**

Adhesive

<b>SECTION 8: Exposure controls/personal protection</b>
---

**8.1. Control parameters****Occupational Exposure Limits**

Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Ethene, homopolymer 9002-88-4 [DUST, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Ethene, homopolymer 9002-88-4 [DUST, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, PARTICULATES]		10	Time Weighted Average (TWA):		EH40 WEL
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, TOTAL VAPOUR AND PARTICULATES]	150	474	Time Weighted Average (TWA):		EH40 WEL

**Occupational Exposure Limits**

Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST]		6	Time Weighted Average (TWA):		IR_OEL
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		IR_OEL
Ethene, homopolymer 9002-88-4 [DUSTS, NON-SPECIFIC, RESPIRABLE]		4	Time Weighted Average (TWA):		IR_OEL
Ethene, homopolymer 9002-88-4 [DUSTS, NON-SPECIFIC, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		IR_OEL
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, PARTICULATES]		10	Time Weighted Average (TWA):		IR_OEL
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, TOTAL (VAPOUR AND PARTICULATES)]	150	470	Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Tetramethylene dimethacrylate 2082-81-7	aqua (freshwater)		0,043 mg/l				
Tetramethylene dimethacrylate 2082-81-7	aqua (marine water)		0,004 mg/l				
Tetramethylene dimethacrylate 2082-81-7	aqua (intermittent releases)		0,098 mg/l				
Tetramethylene dimethacrylate 2082-81-7	sewage treatment plant (STP)		2 mg/l				
Tetramethylene dimethacrylate 2082-81-7	sediment (freshwater)				3,12 mg/kg		
Tetramethylene dimethacrylate 2082-81-7	sediment (marine water)				0,312 mg/kg		
Tetramethylene dimethacrylate 2082-81-7	Soil				0,573 mg/kg		
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	aqua (freshwater)		0,00705 mg/l				
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	aqua (marine water)		0,0007 mg/l				
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	aqua (intermittent releases)		0,0705 mg/l				
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	sediment (freshwater)				0,1729 mg/kg		
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	sediment (marine water)				0,01729 mg/kg		
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Soil				0,057 mg/kg		
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	sewage treatment plant (STP)		10 mg/l				
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	oral				0,119 mg/kg		
2-[[2,2-Bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	aqua (freshwater)		0,0012 mg/l				
2-[[2,2-Bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	Soil				0,096 mg/kg		
2-[[2,2-Bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	sediment (marine water)				0,048 mg/kg		
2-[[2,2-Bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	sediment (freshwater)				0,484 mg/kg		
2-[[2,2-Bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	sewage treatment plant (STP)		100 mg/l				
2-[[2,2-Bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	aqua (intermittent releases)		0,012 mg/l				
2-[[2,2-Bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	aqua (marine water)		0,00012 mg/l				
Fatty acid amide 126098-16-6	aqua (freshwater)		0,000146 mg/l				
Fatty acid amide 126098-16-6	aqua (marine water)		0,0146 g/l				
Fatty acid amide 126098-16-6	aqua (intermittent releases)		0,00025 mg/l				
Fatty acid amide	sediment				5,554		

126098-16-6	(marine water)				mg/kg		
Fatty acid amide 126098-16-6	aqua (freshwater)				55,54 mg/kg		
Fatty acid amide 126098-16-6	Soil				66,576 mg/kg		
Fatty acid amide 126098-16-6	sewage treatment plant (STP)		10 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	aqua (freshwater)		0,0031 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	aqua (marine water)		0,00031 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	aqua (intermittent releases)		0,031 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	Sewage treatment plant		0,35 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	sediment (freshwater)				0,023 mg/kg		
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	sediment (marine water)				0,0023 mg/kg		
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	Soil				0,0029 mg/kg		
Maleic acid 110-16-7	aqua (freshwater)		0,1 mg/l				
Maleic acid 110-16-7	aqua (intermittent releases)		0,4281 mg/l				
Maleic acid 110-16-7	sediment (freshwater)				0,334 mg/kg		
Maleic acid 110-16-7	sewage treatment plant (STP)		44,6 mg/l				
Maleic acid 110-16-7	aqua (marine water)		0,01 mg/l				
Maleic acid 110-16-7	sediment (marine water)				0,0334 mg/kg		
Maleic acid 110-16-7	Soil				0,0415 mg/kg		



## Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Tetramethylene dimethacrylate 2082-81-7	Workers	dermal	Long term exposure - systemic effects		4,2 mg/kg	
Tetramethylene dimethacrylate 2082-81-7	Workers	inhalation	Long term exposure - systemic effects		14,5 mg/m <sup>3</sup>	
Tetramethylene dimethacrylate 2082-81-7	General population	inhalation	Long term exposure - systemic effects		4,3 mg/m <sup>3</sup>	
Tetramethylene dimethacrylate 2082-81-7	General population	dermal	Long term exposure - systemic effects		2,5 mg/kg	
Tetramethylene dimethacrylate 2082-81-7	General population	oral	Long term exposure - systemic effects		2,5 mg/kg	
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Workers	inhalation	Acute/short term exposure - systemic effects		134,4 mg/m <sup>3</sup>	
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Workers	dermal	Long term exposure - systemic effects		1,5 mg/kg	
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Workers	inhalation	Long term exposure - systemic effects		2,12 mg/m <sup>3</sup>	
2-[[2,2-Bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	Workers	Inhalation	Long term exposure - systemic effects		5,88 mg/m <sup>3</sup>	
2-[[2,2-Bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	Workers	dermal	Long term exposure - systemic effects		1,67 mg/kg	
Fatty acid amide 126098-16-6	General population	oral	Long term exposure - systemic effects		8,3 mg/kg	
Fatty acid amide 126098-16-6	General population	dermal	Long term exposure - systemic effects		8,3 mg/kg	
Fatty acid amide 126098-16-6	Workers	dermal	Long term exposure - systemic effects		14 mg/kg	
Fatty acid amide 126098-16-6	General population	inhalation	Long term exposure - systemic effects		2,9 mg/m <sup>3</sup>	
Fatty acid amide 126098-16-6	Workers	inhalation	Long term exposure - systemic effects		9,8 mg/m <sup>3</sup>	
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	Workers	inhalation	Long term exposure - systemic effects		6 mg/m <sup>3</sup>	
Maleic acid 110-16-7	Workers	dermal	Acute/short term exposure - local effects		0,55 mg/cm <sup>2</sup>	
Maleic acid 110-16-7	Workers	dermal	Long term exposure - local effects		0,04 mg/cm <sup>2</sup>	
Maleic acid 110-16-7	Workers	dermal	Acute/short term exposure - systemic effects		58 mg/kg	
Maleic acid 110-16-7	Workers	dermal	Long term exposure - systemic effects		3,3 mg/kg	
Maleic acid 110-16-7	Workers	inhalation	Acute/short term exposure - local effects		3 mg/m <sup>3</sup>	
Maleic acid 110-16-7	Workers	inhalation	Long term exposure - systemic effects		3 mg/m <sup>3</sup>	
Maleic acid 110-16-7	Workers	inhalation	Long term exposure - local effects		3 mg/m <sup>3</sup>	

Maleic acid 110-16-7	Workers	inhalation	Acute/short term exposure - systemic effects	3 mg/m3	
-------------------------	---------	------------	--	---------	--

**Biological Exposure Indices:**

None

**8.2. Exposure controls:****Engineering controls:**

Ensure good ventilation/extraction.

**Respiratory protection:**

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

**Hand protection:**

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to &gt; 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq$  0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to &gt; 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq$  0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

**Skin protection:**

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

Appearance	liquid blue
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	> 93 °C (> 199.4 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	1,7 mbar

(25 °C (77 °F)) Vapour pressure	< 300 mbar
(50 °C (122 °F)) Relative vapour density:	No data available / Not applicable
Density	1,08 g/cm <sup>3</sup>
0 Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Insoluble
Solubility (qualitative) (Solvent: Acetone)	Soluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

**9.2. Other information**

No data available / Not applicable

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Peroxides.

**10.2. Chemical stability**

Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

See section reactivity

**10.4. Conditions to avoid**

No decomposition if used according to specifications.

**10.5. Incompatible materials**

See section reactivity.

**10.6. Hazardous decomposition products**

carbon oxides.

### SECTION 11: Toxicological information

**General toxicological information:**

Prolonged or repeated contact may cause eye irritation.

**11.1. Information on toxicological effects**
**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Tetramethylene dimethacrylate 2082-81-7	LD50	10.066 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
2,4,6-Triallyloxy-s- triazine 101-37-1	LD50	753 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2-[[2,2-bis[[[1-(1- oxoallyl)oxy]methyl]buto xy]methyl]-2-ethyl-1,3- propanediyl diacrylate 94108-97-1	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Fatty acid amide 126098-16-6	LD50	> 2.000 mg/kg	rat	not specified
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	LD50	382 mg/kg	rat	other guideline:
Acetic acid, 2- phenylhydrazide 114-83-0	LD50	270 mg/kg	rat	not specified
maleic acid 110-16-7	LD50	708 mg/kg	rat	not specified
1,4-Naphthalenedione 130-15-4	LD50	190 mg/kg	rat	not specified

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Tetramethylene dimethacrylate 2082-81-7	LD50	> 3.000 mg/kg	rabbit	not specified
2,4,6-Triallyloxy-s- triazine 101-37-1	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
2-[[2,2-bis[[[1-(1- oxoallyl)oxy]methyl]buto xy]methyl]-2-ethyl-1,3- propanediyl diacrylate 94108-97-1	LD50	> 2.000 mg/kg	rat	not specified
Fatty acid amide 126098-16-6	LD50	> 2.000 mg/kg	rat	not specified
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	LD50	530 - 1.060 mg/kg	rat	other guideline:
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	Acute toxicity estimate (ATE)	1.100 mg/kg		Expert judgement
maleic acid 110-16-7	LD50	1.560 mg/kg	rabbit	not specified

**Acute inhalative toxicity:**

No substance data available.  
No data available.

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
maleic acid 110-16-7	irritating	24 h	human	Patch Test

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2-[[2,2-bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	Category II		rabbit	EU Method B.5 (Acute Toxicity: Eye Irritation / Corrosion)
maleic acid 110-16-7	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Tetramethylene dimethacrylate 2082-81-7	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
maleic acid 110-16-7	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
maleic acid 110-16-7	sensitising	Mouse local lymphnode assay (LLNA)	guinea pig	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Tetramethylene dimethacrylate 2082-81-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Tetramethylene dimethacrylate 2082-81-7	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
maleic acid 110-16-7	negative	bacterial reverse mutation assay (e.g Ames test)	no data		Ames Test
maleic acid 110-16-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
maleic acid 110-16-7	not carcinogenic	oral: feed	2 y daily	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
maleic acid 110-16-7	NOAEL F1 150 mg/kg NOAEL F2 55 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure::**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9		inhalation: aerosol	6 h/d 5 d/w	rat	not specified
maleic acid 110-16-7	NOAEL $\geq$ 40 mg/kg	oral: feed	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

**Aspiration hazard:**

No data available.

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	LC50	32,5 mg/l	48 h		DIN 38412-15
2,4,6-Triallyloxy-s-triazine 101-37-1	LC50	4,36 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-[[[2,2-bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	LC50	1,2 mg/l	96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Fatty acid amide 126098-16-6	LC50		96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	LC50	3,9 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
maleic acid 110-16-7	LC50	> 245 mg/l	48 h	Leuciscus idus	DIN 38412-15

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,4,6-Triallyloxy-s-triazine 101-37-1	EC50	19,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-[[[2,2-bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	EC50	> 10 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Fatty acid amide 126098-16-6	EC50		48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	EC50	18 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
maleic acid 110-16-7	EC50	42,81 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	NOEC	5,09 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Fatty acid amide 126098-16-6	NOEC		21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
maleic acid 110-16-7	NOEC	10 mg/l	21 d	Daphnia magna	other guideline:

#### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	EC50	9,79 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Tetramethylene dimethacrylate 2082-81-7	NOEC	2,11 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-[[2,2-bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	EC50	> 12 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-[[2,2-bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	NOEC	< 0,35 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Fatty acid amide 126098-16-6	EC50	0,025 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Fatty acid amide 126098-16-6	NOEC	0,0073 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	ErC50	3,1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
maleic acid 110-16-7	EC50	74,35 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
maleic acid 110-16-7	EC10	11,8 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-Naphthalenedione 130-15-4	EC50	0,011 mg/l	72 h	Dunaliella bioculata	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	NOEC	20 mg/l	28 d	activated sludge, domestic	not specified
2,4,6-Triallyloxy-s-triazine 101-37-1	EC0	5 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Fatty acid amide 126098-16-6	EC50		3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	EC10	70 mg/l	30 min		not specified
maleic acid 110-16-7	EC10	44,6 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)

#### 12.2. Persistence and degradability



Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Tetramethylene dimethacrylate 2082-81-7	readily biodegradable	aerobic	84 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO <sub>2</sub> in Sealed Vessels (Headspace Test))
2,4,6-Triallyloxy-s-triazine 101-37-1		aerobic	7 - 9 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO <sub>2</sub> Evolution Test)
2-[[[2,2-bis[[[1- oxoallyl]oxy]methyl]butoxy] methyl]-2-ethyl-1,3- propanediyl diacrylate 94108-97-1		aerobic	4 - 14 %	29 d	OECD Guideline 301 B (Ready Biodegradability: CO <sub>2</sub> Evolution Test)
Fatty acid amide 126098-16-6	not readily biodegradable.	aerobic	7 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO <sub>2</sub> Evolution Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9		no data	0 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO <sub>2</sub> Evolution Test)
maleic acid 110-16-7	readily biodegradable	aerobic	97,08 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO <sub>2</sub> Evolution Test)
1,4-Naphthalenedione 130-15-4	not readily biodegradable.	no data	0 - 60 %		OECD 301 A - F

### 12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	9,1			calculation	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

### 12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Tetramethylene dimethacrylate 2082-81-7	3,1		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
2,4,6-Triallyloxy-s-triazine 101-37-1	2,8	20 °C	not specified
2-[[2,2-bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	4,14	30 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Fatty acid amide 126098-16-6	> 6,5	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	2,16		not specified
Acetic acid, 2-phenylhydrazide 114-83-0	0,74		not specified
maleic acid 110-16-7	-1,3	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
1,4-Naphthalenedione 130-15-4	1,71		not specified

#### 12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Tetramethylene dimethacrylate 2082-81-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2,4,6-Triallyloxy-s-triazine 101-37-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-[[2,2-bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Fatty acid amide 126098-16-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
maleic acid 110-16-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
1,4-Naphthalenedione 130-15-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

#### 12.6. Other adverse effects

No data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Collection and delivery to recycling enterprise or other registered elimination institution.

##### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

##### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

<b>SECTION 14: Transport information</b>
--

**14.1. UN number**

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

**14.2. UN proper shipping name**

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Fatty acid amide)

**14.3. Transport hazard class(es)**

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

**14.4. Packing group**

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

**14.5. Environmental hazards**

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

**14.6. Special precautions for user**

ADR	not applicable Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content < 3 %  
(2010/75/EC)

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.  
H301 Toxic if swallowed.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H331 Toxic if inhaled.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.